



NOTES:

- PLATING  
ELECTRO Ni : 2.00~6.00 MICRON.  
ELECTRO Au : 0.70~1.20 MICRON.
- CAMBER : ±50.00 MICRON MAX.
- CONNECTION :  
(1-4), (2-5), (3-ENABLE), (6-9-VSS-S/R), (7-VDD), (8-OUTPUT).
- GENERAL TOLERANCE : ±1% N.L.T. ±0.13
- STRESS RELAXATION DESIGN SHALL BE APPLIED ON THIS ITEM.
- EXPOSURE OF CERAMIC SURFACE AND METALLIZED PATTERN OCCURRED BY MISALIGNMENT OF THE UPPER LAYER, SHALL BE ALLOWED.
- PART TO BE SHOWN AS SIDE METALLIZED PATTERN.
- SEALING METHOD OF THIS PRODUCT SHALL BE SEAM WELD.
- AIR BLOW SPECIFICATIONS.

TOLERANCE	REVISION	SEE ATTACHED EXCEPTIONS SHEET.			TITLE	
±1% N.L.T.±0.13 ANGLES	SCALE	DIMENSION	PROJECTION	CUSTOMER DWG NO.	REV.	5.0X3.2 OSC PKG
	20 : 1	mm	3rd			
MATERIAL	APPROVED	CHECKED	ENGRG	CHECKED	DESIGNED	PART NO.
90%MIN.A1203 (NA-311B BLACK)						S5032CLK2
						REV. 0
						DWG NO.
						SHT/OF 1/7

**PRELIMINARY**