



- NOTES**
- PLATING  
 ELECTRO Ni : 2.00 ~ 6.00 MICRON.  
 ELECTRO Au : 0.70 ~ 1.20 MICRON.
  - CAMBER : 50.00 MICRON MAX.
  - CONNECTION :  
 (1-9), (2-3), (4-D-S/R), (5-6-G),  
 (7-H-D/A), (8-C), (A-B-B-F-N/C)
  - GENERAL TOLERANCE : ±1% N.L.T. ±0.13
  - EXPOSURE OF CERAMIC SURFACE AND METALLIZED PATTERN OCCURRED BY MISALIGNMENT OF THE UPPER LAYER, SHALL BE ALLOWED.
  - PART TO BE SHOWN AS SIDE METALLIZED PATTERN.
  - SEALING METHOD OF THIS PRODUCT SHALL BE SEAM WELD.

TOLERANCE	REVISION	SEE ATTACHED EXCEPTIONS SHEET.				TITLE
±1% ±0.13 N.L.T. ANGLES	SCALE	DIMENSION	PROJECTION	CUSTOMER DWG NO.	REV.	7050 OSC A
	15 : 1	mm	3rd			PART NO. S5070CLK4
MATERIAL	APPROVED	CHECKED	ENGRG	CHECKED	DESIGNED	REV. 0
90%MIN. Al <sub>2</sub> O <sub>3</sub> (NA-301B BLACK)	Shigetomi	Yamahata	Ohba	Kumura	Kanazawa	DWG NO. 1/8
	Mar.06.02	Mar.06.02	Mar.05.02	Mar.05.02	Mar.05.02	